Wireflow




0303


Design By Arik Levy

Wireflow designed by Arik Levy. A hanging lamp which reviews and updates the chandelier look through an exercise of simplification that explores its essence and enhances its outline with great delicacy and at the same time a strong formal presence. Its appearance, as a structure of fine cables finished with eight LED terminals, discretely connects with classic chandelier models, taking this type of lamp to a new, groundbreaking and futuristic dimension. Employing CREA product configurator software, the design can be modified to adapt to your specific project requirements.

Model Sheet







Optional: Extra cable length

Min. quantity, upcharge and extra lead time apply [EN]



LED temperature 2700 K / 3000 K / **color** 3500 K

Instalation type

Dimming Casambi / Push; 1-10V; DALI-2

Materials	Ceiling rose: Steel
	Body: Aluminum
	Horizontal rods: Steel
Light source	8 x LED 4,48W 350mA

Surface Canopy

Driver Constant Current 350 110~240 V V 50~60 Hz HZ

Dimmable LED

IP20 Bi-volt 50-60Hz

2700 K / 3000 K / 3500 K

Application Hanging lamps

Packaging 2 Box 0.6 m x 0.6 m x 0.27 m Gross weigth 11.9 Net weigth 9.25 Vol. 0.1558




Lighting effect


Volumetric Diffuser

Subtly directed, diffused light that generates a soft hierarchy of light on to the illuminated surface




Photometric Data





Efficiency 40.11%
Coordinate System CG
Total Flux 2941.60
Maximum Value 53.87

Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty