Wireflow lineal




0320


Design By Arik Levy

Wireflow designed by Arik Levy. Linear hanging lamp Its appearance, as a structure of fine cables finished with two 4,5W LED terminals, is ideal for discretely connecting with classic chandelier models, taking this type of lamp to a new, groundbreaking and futuristic dimension. Employing CREA product configurator software, the design can be modified to adapt to your specific project requirements. Ideal for decorating large spaces, particularly ones with high ceilings, including hotel reception areas, retail sales points and food and drinks bars.

Model Sheet







Optional : Extra cable length
Min. quantity, upcharge and extra lead time
apply [EN]

Finish O4 Black RAL 9005

LED temperature color

2700 K / 3000 K / 3500 K

Dimming

Casambi / Push; 1-10V / DALI

Instalation type	Surface
------------------	---------

Materials

Body: Aluminum

Horizontal rods: Steel

Ceiling rose: Aluminum

Light source 2 x LED 4,48W 350mA

LED CRI>90 981 lm 109 2700 K / 3000 K / 3500 K

2700 K7 3000 K7 3300 I

Driver Constant Current 350 110~240 V V 50~60 Hz HZ

Remarks Linear canopy

IP20 Bi-volt 50-60Hz

Application Hanging lamps

Packaging 1Box

0.7 m x 0.2 m x 0.075 m Gross weigth 2.7 Net weigth 0.6 Vol. 0.0105


Lighting effect


Hidden Diffuser

Subtly directed diffused light that generates a soft hierarchy of light on to the illuminated surface




Photometric Data





Efficiency Coordinate System Total Flux Maximum Value 46.23% CG 980.60 320.25

Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty