# Wireflow lineal



### 0325


Design By Arik Levy

Wireflow designed by Arik Levy. Linear hanging lamp Its appearance, as a structure of fine cables finished with six 4,5W LED terminals, is ideal for discretely connecting with classic chandelier models, taking this type of lamp to a new, groundbreaking and futuristic dimension. Employing CREA product configurator software, the design can be modified to adapt to your specific project requirements. Ideal for decorating large spaces, particularly ones with high ceilings, including hotel reception areas, retail sales points and food and drinks bars.

## Model Sheet







Optional : Extra cable length
Min. quantity, upcharge and extra lead time
apply [EN]

# Finish O4 Black RAL 9005

LED temperature color

2700 K / 3000 K / 3500 K

Dimming

DALI / Push; 1-10V / Casambi

## Instalation type Surface Canopy

Materials Body: Steel

Horizontal rods: Steel Ceiling rose: Aluminum

Light source 6 x LED 4,48W 350mA

LED CRI>90 2942 lm 109 2700 K / 3000 K / 3500 K

Driver Constant Current 350 110~240

V V 50~60 Hz HZ

Remarks Linear canopy

 $\begin{tabular}{ll} $\searrow$ \hline $\not \end{tabular} \begin{tabular}{ll} $\searrow$ \hline $\o$ \hline \end{tabular} \begin{tabular}{ll} $\downarrow$ \hline \end{tabu$ 

IP20 Bi-volt 50-60Hz

Application Hanging lamps

Packaging 1 Box

2.3 m x 0.2 m x 0.075 m Gross weigth 7.6 Net weigth 5.3 Vol. 0.0345


#### Lighting effect


#### Hidden Diffuser

Subtly directed diffused light that generates a soft hierarchy of light on to the illuminated surface




#### Photometric Data





Efficiency Coordinate System Total Flux Maximum Value 46.23% CG 2941.60 320.26

### Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty