Wireflow lineal




0330


Design By Arik Levy

Wireflow designed by Arik Levy. Linear hanging lamp Its appearance, as a structure of fine cables finished with ten 4,5W LED terminals, is ideal for discretely connecting with classic chandelier models, taking this type of lamp to a new, groundbreaking and futuristic dimension. Employing CREA product configurator software, the design can be modified to adapt to your specific project requirements. Ideal for decorating large spaces, particularly ones with high ceilings, including hotel reception areas, retail sales points and food and drinks bars.

Model Sheet







Optional: Extra cable length Min. quantity, upcharge and extra lead time apply [EN] Finish 04 Black RAL 9005

LED temperature 2700 K / 3000 K / **color** 3500 K

Dimming Casambi / DALI / Push; 1-10V

Instalation type Surface Canopy

Materials Body: Aluminum
Horizontal rods: Steel
Ceiling rose: Aluminum

Light source 10 x LED 4,5W 700mA

D)

LED CRI>90 4903 lm 109 2700 K / 3000 K / 3500 K

Driver Constant Current 700 220~240 V V 50~60 Hz HZ

Remarks Linear canopy

 $\begin{tabular}{ll} \searrow \hline $\not \end{tabular} \begin{tabular}{ll} \square \hline \end{tabular} \$

[P20] [50-60Hz]

Application Hanging lamps

Packaging 1 Box

3.3 m x 0.2 m x 0.075 m Gross weigth 11.5 Net weigth 9.5 Vol. 0.0495


Lighting effect


Hidden Diffuser

Subtly directed diffused light that generates a soft hierarchy of light on to the illuminated surface




Photometric Data





Efficiency Coordinate System Total Flux Maximum Value 46.23% CG 4903.00 lm 320.25 cd/klm

Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty