# Wireflow free-form



## 0345

Design By Arik Levy

Wireflow designed by Arik Levy. Hanging lap. The elegant structure of fine cables and LED terminal by Wireflow allows the combination of multiple individual pieces to carry out major graphic lighting installations which generate a visual opportunity of lines and points of light and bring a markedly conceptual character to an intangible product. Employing CREA product configurator software, the design can be modified to adapt to your specific project requirements. The electrical connection point can be positioned on the ceiling or wall

# Model Sheet







Optional: Extra cable length
Min. quantity, upcharge and extra lead time
apply [EN]

Finish 04 Black RAL 9005

LED temperature 2700 K / 3000 K / 3500 K

Dimming

Instalation type Remote XXS / Surface Free Wire /

Push; 1-10V / DALI-2 / Casambi

Surface Canopy / Built-in XS

Materials Rods: Steel Body: Aluminum

Ceiling rose: Steel

Light source 1x LED 4,5W 700mA

D

LED CRI>90 490 lm 109 2700 K / 3000 K / 3500 K

Driver Constant Current 700 100~240

V V 50~60 Hz HZ

IP20 Bi-volt 50-60Hz

Application Hanging lamps

Packaging 1 Box

0.26 m x 0.26 m x 0.26 m Gross weigth 2.6 Net weigth 2.4 Vol. 0.0175


## Lighting effect


### Volumetric Diffuser

Subtly directed, diffused light that generates a soft hierarchy of light on to the illuminated surface



### Photometric Data





Efficiency 40.10%
Coordinate System CG
Total Flux 490.30
Maximum Value 53.76

Other Applications

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty