
# Algorithm




Design By Toan Nguyen



## Model Sheet







Optional : Extra cable length Min. quantity, upcharge and extra lead time apply [EN]

Finish



18 Graphite ADAPTA RF 9913 WX

LED temperature color

2700 K / 3500 K

Dimming

Push; 1-10V; DALI-2 / Casambi

Instalation type

Surface Canopy

Materials

Sphere: Blown glass Glass fastening: Aluminum Diffuser: PC- Polycarbonate Pendant structure: Steel

Light source

10 x LED 3,15W 1050mA

LED

CRI>90 3123 lm 99 2700 K / 3500 K

Driver

Constant Current 1050 100~240 V V 50~60 Hz HZ

Remarks

The steel cables that go from the structure to the ceiling are the only ones that allow the height of the lamp to be adjusted. The installation manual describes how to do this and how to cut the

The 25 cm fixing bars are included









Hanging lamps

**Application Packaging** 

2 Box

1.089 m x 1.089 m x 0.18 m Gross weigth 14.3

Net weigth 10.5 Vol. 0.3344


#### Lighting effect


#### Volumetric Diffuser

Subtly directed, diffused light that generates a soft hierarchy of light on to the illuminated surface



#### Photometric Data






Efficiency Coordinate System **Total Flux** Maximum Value

CG 3122.80 lm 142.75 cd/klm

### Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

