Algorithm


0830


Design By Toan Nguyen

Pendant light fitting designed by Toan Nguyen. Composed of a collection of hand blown glass spheres with LED light source suspended at different heights, anchored to the ceiling via a floating tubular structure. Available with ceiling rose or built-in. The finishes are matt graphite and matt white.

Model Sheet







Optional: Extra cable length Min. quantity, upcharge and extra lead time apply [EN]

Finish



18 Graphite ADAPTA RF 9913 WX

LED temperature color

2700 K / 3500 K

Dimming

Casambi / Push; 1-10V; DALI-2

Instalation type

Surface Canopy

Materials

Sphere: Blown glass Glass fastening: Aluminum Diffuser: PC- Polycarbonate Pendant structure: Steel

Light source

6 x LED 3,15W 1050mA

LED

CRI>90 1873 lm 99 2700 K / 3500 K

Driver

Constant Current 1050 100~240 V V 50~60 Hz HZ

Remarks

Request built-in canopy at www.vibia.com

The steel cables that go from the structure to the ceiling are the only ones that allow the height of the lamp to be adjusted. The installation manual describes how to do this and how to cut the







[IP20] [Bi-volt] [50-60Hz]

Application

Hanging lamps

Packaging

2 Box 1.3 m x 0.499 m x 0.18 m Gross weigth 9.3 Net weigth 5.8

Vol. 0.1756


Lighting effect


Volumetric Diffuser

Subtly directed, diffused light that generates a soft hierarchy of light on to the illuminated surface



Photometric Data





Efficiency Coordinate System **Total Flux** Maximum Value

49 59% CG 1873 lm 137.10 cd/klm

Other Applications



All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty