Duo

\vee | 3 | \wedge

4874

Design By Ramos & Bassols

Duo is a ceiling light with surface installation where the natural warm appearance of the oak wood on the inside is combined with the technical refinement of the aluminium metal wrap on the outside.

Finish

93 White


RAL 9016

Model Sheet






Instalation type Surface Canopy Materials Shade: Wood Light source 1 x LED PLATE 12W 350mA G LED CRI>90 1100 Im 91.66 2700 K / 3500 K Driver Constant Current 350 110~2 V V 50~60 Hz HZ G Bi-volt 50-60Hz Application Ceiling Lamps Packaging 1 Box 0.436 m x 0.436 m x 0.348	RAL 7044 LED temperature color 2700 K / 3500 K Dimming DALI-2 / Casambi / Push; 1-14 Instalation type Surface Canopy Materials Shade: Wood Light source 1 x LED PLATE 12W 350mA G Immode LED CRI>90 1100 lm 91.66 2700 K / 3500 K Driver Constant Current 350 110~24 V V 50~60 Hz HZ Immode IP20 Bi-volt 50-60Hz Application Ceiling Lamps Packaging 1 Box		18 Graphite ADAPTA RF 9913 WX	
Leb Color Dimming DALI-2 / Casambi / Push; 1- Instalation type Surface Canopy Materials Shade: Wood Light source 1 x LED PLATE 12W 350mA G Imming LED CRI>90 1100 Im 91.66 2700 K / 3500 K Driver Constant Current 350 110-2 V V 50~60 Hz HZ Immable IP20 Bi-volt 50-60Hz Application Ceiling Lamps Packaging 1 Box 0.436 m x 0.436 m x 0.348	Leb of color Dimming DALI-2 / Casambi / Push; 1-1 Instalation type Surface Canopy Materials Shade: Wood Light source 1 × LED PLATE 12W 350mA G Image: CRI>90 1100 Im 91.66 LED CRI>90 1100 Im 91.66 Driver Constant Current 350 110~24 V V 50~60 Hz HZ V V 50~60 Hz HZ Driver Constant Current 350 110~24 V V 50~60 Hz HZ V 0 50~60 Hz HZ Application Ceiling Lamps Packaging 1 Box 0.436 m x 0.436 m x 0.348 m Gross weigth 6 Net weigth 4			
Instalation type Surface Canopy Materials Shade: Wood Light source 1 × LED PLATE 12W 350mA G LED CRI>90 1100 lm 91.66 2700 K / 3500 K Driver Constant Current 350 110~2 V V 50~60 Hz HZ Q Bi-volt 50-60Hz Application Ceiling Lamps Packaging 1 Box 0.436 m × 0.436 m × 0.348	Instalation type Surface Canopy Materials Shade: Wood Light source 1 × LED PLATE 12W 350mA G LED CRI>90 1100 Im 91.66 2700 K / 3500 K Driver Constant Current 350 110~24 V V 50~60 Hz HZ Q V V 50~60 Hz HZ Application Ceiling Lamps Packaging 1 Box 0.436 m x 0.436 m x 0.348 n Gross weigth 6 Net weigth 4		2700 K / 3500 K	
Materials Shade: Wood Light source 1 x LED PLATE 12W 350mA G G LED CRI>90 1100 lm 91.66 2700 K / 3500 K Driver Constant Current 350 110~2 V V 50~60 Hz HZ Immable IP20 Bi-volt 50-60Hz Application Ceiling Lamps Packaging 1 Box 0.436 m x 0.436 m x 0.348	Materials Shade: Wood Light source 1 x LED PLATE 12W 350mA G G LED CRI>90 1100 lm 91.66 2700 K / 3500 K Driver Constant Current 350 110~24 U F Dimmable IP20 Bi-volt 50-60Hz Application Ceiling Lamps Packaging 1 Box 0.436 m x 0.436 m x 0.348 m Gross weigth 6	Dimming	DALI-2 / Casambi / Push; 1-10\	
Light source 1 x LED PLATE 12W 350mA Image: Constant Current 350 1100 lm 91.66 2700 K / 3500 K Driver Constant Current 350 110~2 V V 50~60 Hz HZ Umage: Constant Current 350 110~2 Image: Constant Current 350 110~2 V V 50~60 Hz HZ Image: Constant Current 350 110~2 V V 50~60 Hz HZ Image: Constant Current 350 110~2 Image: Constant Current 350 110~2 Image: Constant Current 350 110~2 V V 50~60 Hz HZ Image: Constant Current 350 110~2 Image: Constant Current 350 110~2 Image: Constant Current 350 110~2 Image: Constant Current 350 110~2 Image: Constant Current 350 110~2 Image: Constant Current 350 110~2 Image: Constant Current 350 110~2 Image: Constant Current 350 110~2 Image: Constant Current 350 110~2 Image: Constant Current 350 110~2 Image: Constant Current 350 110~2 Image: Constant Current 350 110~2 Image: Constant Current 350 110~2 Image: Constant Current 350 110~2 Image: Constant Current 350 110~2 Image: Constant Current 350 110~2 Image: Constant Current 350 110~2 Image: Constant Current 350 110~2 Image: Constant Current 350 110~2 Image: Constant Current 350 110~2 Image: Constant Current 350 110~2 Image:	Light source 1 × LED PLATE 12W 350mA G LED CRI>90 1100 lm 91.66 2700 K / 3500 K Driver Constant Current 350 110~24 V V 50~60 Hz HZ G K/ Dimmable [IP20] Bi-volt 50-60Hz Application Ceiling Lamps Packaging 1 Box 0.436 m × 0.436 m × 0.348 m Gross weigth 6 Net weigth 4	Instalation type	Surface Canopy	
Is in course G LED CRI>90 1100 lm 91.66 2700 K / 3500 K Driver Constant Current 350 110~2 V V 50~60 Hz HZ Image: Constant Current 350 110~2 Image: Constant 10~2 Image: Constant 10~2<	G LED CRI>90 1100 lm 91.66 2700 K / 3500 K Driver Constant Current 350 110~24 V V 50~60 Hz HZ Uriver V 50~60 Hz HZ Bi-volt 50-60Hz Bi-volt 50-60Hz Application Ceiling Lamps Packaging 1 Box 0.436 m x 0.436 m x 0.348 n Gross weigth 6 Net weigth 4	Materials	Shade: Wood	
2700 K / 3500 K Driver Constant Current 350 110~2 V V 50~60 Hz HZ Image: Constant Current 350 110~2 V V 50~60 Hz HZ Image: Constant Current 350 110~2 Image: Constant 35	2700 K / 3500 K Driver Constant Current 350 110~24 V V 50~60 Hz HZ Image: Solution of the second se	Light source		
V V 50~60 Hz HZ Image: Stress of the stre	V V 50~60 Hz HZ	LED		
Bi-volt 50-60Hz Application Ceiling Lamps Packaging 1 Box 0.436 m x 0.436 m x 0.348	Bi-volt 50-60Hz Application Ceiling Lamps Packaging 1 Box 0.436 m x 0.436 m x 0.348 m Gross weigth 6 Net weigth 4	Driver	Constant Current 350 110~240 V V 50~60 Hz HZ	
Packaging 1 Box 0.436 m x 0.436 m x 0.348	Packaging 1 Box 0.436 m x 0.436 m x 0.348 n Gross weigth 6 Net weigth 4			
0.436 m x 0.436 m x 0.348	0.436 m x 0.436 m x 0.348 n Gross weigth 6 Net weigth 4	Application	Ceiling Lamps	
Net weigth 4		Packaging	0.436 m x 0.436 m x 0.348 m Gross weigth 6 Net weigth 4	



First layer of basic, general illumination

Lighting effect

General



Other Applications



Ø 35 cm

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty

Vibia Lighting, S.L.U.

Office / Oficina Progrés 4-6. 08850 Gavà. Barcelona, Spain.

International T +34 934 796 971 Spain / Portugal T +34 934 796 970 customer.service@vibia.com vibia.com