



SPURBMIG
Design by Dima Loginoff

Collection consisting of aluminium ceiling lamps and suspended lamps.
Available in several colours and sizes.


Typology: SUSPENSION LAMP

Ratings

- Built in line voltage **LED** module
- CCT 3000 K
- Downlight
- Surface installation over holes
- Supply voltage ~220-240V
- Switch mode: on-off, dimmable trailing edge
- Aluminium body, painted
- Diffuser

SP URB MI G

kg 0,5 m³ 0,04



Product code composition

URBAN MINI / solo con illuminazione verso il basso / downward lighting only

Type	Article	Colours	Finishing	Source
SP	URB MI G	BC wrinkled white BR matt bronze NI matt nickel	XX	LED 8W - diffused beam 2700K 4000K


CE IP20 CRI90  220-240VAC **LED** (~640 lm* ~80 lm/W* 3000K*)

example composition code SP URB MI G NI XX LED


Available colors



BC
Wrinkled
white



BR
Matt
bronze



NI
Matt
nickel

SPURBMIG _ _ XXLED

CUSTOMER _____ NOTES _____

NOTICE:

Luminous flux (lm) and efficacy (lm/W) for all LED luminaires is based on nominal ratings of the LED sources.
Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.