

## Technical data

Rated voltage	230V AC
Input voltage range	220 - 240 V AC
Driver output	-
Alimentation output	-
Class	1
IP	44
IK	10
Diffuser	Satin-finish PMMA
Bulb cover	No
Source	GU10 PAR16 LED
Color temperature real output	-
Real light output	- lm
Total consumption	- W
Energy class	Classe de la lampe (non fournie)
Luminous efficacy	-
IRC	-
SDCM	-
Optic	-
Dimmable	-
Ta	-
Led lifetime	-
Ambient temperature range	-10 ~50°C
UGR	-
ULR	-
Photobiological Risk group	RG2
THDI	-
Fixing kit	Yes
With sensor	No
With IP55 socket	No

[Download the installation manual](#)



## Materials and finishes

Material	aluminium
Colour	Jet black - 000 - RAL 9005

## Logistic data

Product dimensions	H.600 L.260 P.183
Net weight	2.710 Kg
Gross weight	3.860 Kg
Package dimensions 1	H.630 L.380 P.240

## Certifications and warranties

CE	Pour fiche Média
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	5 years

## Technical data

Rated voltage	230V AC
Input voltage range	120 - 277 V AC
Class	1
IP	65
IK	10
Diffuser	Satin-finish PMMA
Bulb cover	No
Source	Built-in LED
Color temperature real output	3000°K warm white
Real light output	1952 lm
Total consumption	26 W
Energy class	C (Source LED)
IRC	>80
SDCM	4
Dimmable	No
Ta	-
Ambient temperature range	-10 ~50°C
UGR	-
ULR	-
Photobiological Risk group	RG2
Fixing kit	Yes
With sensor	No
With IP55 socket	No

[Download the installation manual](#)



## Materials and finishes

Material	aluminium
Colour	Jet black - 000 - RAL 9005

## Logistic data

Product dimensions	H.600 L.260 P.183
Net weight	3.190 Kg
Gross weight	4.250 Kg
Package dimensions 1	H.630 L.380 P.240

## Certifications and warranties

CE	Pour fiche Média
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	5 years