CTOLIGHTING

TREVI PENDANT SMALL

FINISH

antique bronze with matt opal glass bronze with matt opal glass satin brass with matt opal glass

DIMENSIONS (body of fixture)

1100 x 950 x 265 mm (w x d x h)

WEIGHT

6kg (13.2lbs)

please ensure ceiling structure is strong enough to support the weight of the light

OVERALL DROP

minimum 375 mm supplied with 1000mm drop rod (12.7mm dia) as standard (adjustable on site)

ILLUMINATION

220-240v - 3 x E14 - 25w max (or 4.5w LED 2700k) 110-130v - 3 x E12 - 25w max (or 4.5w LED 2700k)

DIMMING

dimmable bulb required trailing edge dimmable / phase cut (rotary dimmer) - standard DALI option available (220-240v only)

CEILING ROSE / PLATE

round ceiling rose - ø 116 x 25 mm (dia x h)

CERTIFICATION









VIEW ON WEBSITE










mounting plate dimensions



^{*}Diagrams are not to scale.

CTOLIGHTING

TREVI PENDANT SMALL - DALI-A

FINISH

antique bronze with matt opal glass bronze with matt opal glass satin brass with matt opal glass

DIMENSIONS (body of fixture)

1100 x 950 x 265 mm (w x d x h)

WEIGHT

6kg (13.2lbs)

please ensure ceiling structure is strong enough to support the weight of the light

OVERALL DROP

minimum 375 mm supplied with 1000mm drop rod (12.7mm dia) as standard (adjustable on site)

ILLUMINATION

220-240v - 3 x E14 - 25w max (or 4.5w LED 2700k) DALI converter to be installed in the ceiling rose

DIMMING

dimmable bulb required DALI compatible

CEILING ROSE / PLATE

round ceiling rose - ø 116 x 25 mm (dia x h)


CERTIFICATION






VIEW ON WEBSITE










mounting plate dimensions



^{*}Diagrams are not to scale.

CTOLIGHTING

TREVI PENDANT SMALL - DALI-B

FINISH

antique bronze with matt opal glass bronze with matt opal glass satin brass with matt opal glass

DIMENSIONS (body of fixture)

1100 x 950 x 265 mm (w x d x h)

WEIGHT

6kg (13.2lbs)

please ensure ceiling structure is strong enough to support the weight of the light

OVERALL DROP

minimum 385 mm supplied with 1000mm drop rod (12.7mm dia) as standard (adjustable on site)

ILLUMINATION

220-240v - 3 x E14 - 25w max (or 4.5w LED 2700k) DALI converter to be installed in the ceiling rose

DIMMING

dimmable bulb required DALI compatible

CEILING ROSE / PLATE

round ceiling rose - ø 140 x 35 mm (dia x h)


CERTIFICATION







VIEW ON WEBSITE











^{*}Diagrams are not to scale.



TREVI PENDANT SMALL

TREVI PENDANT SMALL

SKU NUMBER	FINISH DESCRIPTION	VOLTAGE
TREPESABMO-240	antique bronze with matt opal glass	220 - 240V
TREPESBZMO-240	bronze with matt opal glass	220 - 240V
TREPESSBMO-240	satin brass with matt opal glass	220 - 240V
TREPESABMO-110	antique bronze with matt opal glass	110 - 130V
TREPESBZMO-110	bronze with matt opal glass	110 - 130V
TREPESSBMO-110	satin brass with matt opal glass	110 - 130V

TREVI PENDANT SMALL - DALI-A

SKU NUMBER	FINISH DESCRIPTION	TYPE OF DALI	VOLTAGE
TREPESABMO-DALIA-240	antique bronze with matt opal glass	DALI A included - For lights that do not require aesthetic alterations. Dali can be fitted inside the ceiling/wall rose	220 - 240V
TREPESBZMO-DALIA-240	bronze with matt opal glass	DALI A included - For lights that do not require aesthetic alterations. Dali can be fitted inside the ceiling/wall rose	220 - 240V
TREPESSBMO-DALIA-240	satin brass with matt opal glass	DALI A included - For lights that do not require aesthetic alterations. Dali can be fitted inside the ceiling/wall rose	220 - 240V

TREVI PENDANT SMALL - DALI-B

SKU NUMBER	FINISH DESCRIPTION	TYPE OF DALI	VOLTAGE
TREPESABMO-DALIB-240	antique bronze with matt opal glass	DALI B included - The light will feature a deeper ceiling/wall rose. For use when there is no space in the existing ceiling/wall cavity	220 - 240V
TREPESBZMO-DALIB-240	bronze with matt opal glass	DALI B included - The light will feature a deeper ceiling/wall rose. For use when there is no space in the existing ceiling/wall cavity	220 - 240V
TREPESSBMO-DALIB-240	satin brass with matt opal glass	DALI B included - The light will feature a deeper ceiling/wall rose. For use when there is no space in the existing ceiling/wall cavity	220 - 240V